

19" 1U PC Patch Panel 24xRJ45/u, Cat. 6A EL, black, fully populated

DESCRIPTION



PRODUCT_IMAGE

SCOPE OF SUPPLY

- 19" 1U 24-port patch panel, empty, unshielded
- 24 RJ45 Cat. 6A EL connection modules, unshielded and dust covers
- 19" mounting kit
- 4 labeling strips
- Cable ties
- Installation instructions

TENDER

Modular patch panel with integrated cable tie shelf, 19" fastening kit, labeling fields with exchangeable labeling strips. The ports are prepared for a visual color coding system and automated infrastructure management systems. Panel polycarbonate, fiber-glass-reinforced, halogen-free material, UL 94 listed and steel: DC01 (1.0330), 1.5 mm. Color front: black (RAL 9005) / steel: blue, chromitized.

RJ45 connection module of Cat. 6A EL, for the setting up of transmission channels of Class EA with up to 4 connectors acc. to ISO/IEC 11801, EN 50173-1, (DIN EN 50173-1), complies with Cat. 6A requirements of the standards ISO/IEC 11801, EN 50173-1 as well the U.S. standard Cat. 6A according to TIA/EIA 568.2-D, re-embedded tested in acc. with IEC 60603-7-41 and 60512-27-100, interoperable and backwards compatible with Category 6 and Category 5e.

Suitable for 10GBASE-T applications in acc. with IEEE 802.3™ Section Four up to 500 MHz and 100 m.

Tested in line with R&M's manufacturing control, performing 100% inspection. Each module has an own serial number and is traceable.

Compatible with RJ standard plugs (RJ11, RJ12, RJ45), connection of installation cables AWG 26 22 (0.4 mm 0.65 mm) and flexible cables AWG 26/7 AWG 22/7 without special tools. Parallel pair termination without crossover in acc. with TIA 568-A/B, gold-plated bronze contacts for >1000 mating cycles, IDC contacts with ≥4 insertion cycles acc. to IEC 60352-3, contact resistance <5 mOhm, dielectric strength >1000 Veff. Supports PoE (IEEE 802.3af), PoEP (IEEE 802.3at), 4Ppoe (IEEE 802.3bt) and is compatible to IEC 60512-99-001/002. With integral cable strain relief, including dust cover. Red / black plastic housing.

Material: halogen-free and heavy-metal free in acc. with EU directives RoHS 2.

Connection module Cat. 6A EL, red / black, unshielded and dust cover.

TECHNICAL DATA











DESCRIPTION	VALUE / VALUE RANGE
Number of connectors (A)	24
Category connector (A)	Cat. 6A ISO
Connector type (A)	RJ45
Shielding connector (A)	unshielded

Protection class IP	IP 20
PoE	Yes
Amount of height units	1 U
Rack mounting version	patch panel
Assembly	fully populated
Holder for connector / module	Special (without mounting plate)
Capacity (ports)	24
Standard	IEC 60603-7-41: Electrical Characteristics of the Telecommunication Outlets
Amount of height units	1 U
Fastening	19 "

MECHANICAL DATA

DESCRIPTION	VALUE / VALUE RANGE
Dimensions	482.6 mm x 43.65 mm x 83.4 mm / 19 in x 1.719 in x 3.283 in (W x H x D)
Color	front, black (RAL 9005) / steel, blue, chromated
Material	plastic: PC, fiber-glass reinforced / steel: DC01 (1.0330), 1.5 mm

ACCESSORIES

Type	Picture	Description	Article	E-Number
Accessories		Labeling Sheet Fiberliner / 3U Global Mo	R30871	966730495
Accessories		Patching Ring left / right, 75 mm, gray	R302005	966791005
Accessories		Clip Security Level 1 PC PP IP20 red	R810639	977901765
Accessories		Clip Security Level 1 PC PP IP20 green	R810640	977901775
Accessories		Clip Security Level 1 PC PP IP20 yellow	R812460	977901755
Accessories		Clip Security Level 1 PC PP IP20 blue	R812461	977901725
Accessories		Basic Blind Cover, white	R812462	966732295
Accessories		inteliPhy Monitor Sensorbar for PC panel	R812772	
Accessories		Clip Security Level 1 PC PP IP20 gray	R820300	
Accessories		Clip Security Level 1 PC PP IP20 brown	R832236	