

W35 Indoor/Outdoor Lockable Wall Box - up to 12 Fibers SC Simplex or LC Duplex Adaptor

This Lockable IP65 distribution box is supplied loaded or unloaded and offers the ability to terminate up to 12 Fibers SC Simplex or LC Duplex adapter housed in a strong robust ABS enclosure for indoor and outdoor applications. An internal detachable tray provides a neat and tidy solution for housing 12 SC simplex and LC duplex connections and splices. The box has 12 patch cord exit points and up to 2 cable entry points which maintain the IP65 rating. Integrated cable tie points are included to secure incoming cables. A locking feature for the door adds extra security when positioned in un-secure area



Features

- IP 65 Rating for external use
- Lockable door for added security
- Integrated cable tie points for securing incoming cable
- Up to 12 splice SC Simplex or LCDuplex connection points
- Removable splice tray for easy installation
- Accepts loose tube, distribution and pre-terminated cables
- Integrated bend radius protection
- Sealing glands for up to 12 exiting cables + 2 x 6.5mm-13mm incoming cable
- Removable door for ease of installation
- Supplied with 12 heatshrink splice protectors
- Supplied with transit tubing
- Supplied with wall fixings and tie wraps
- ROHS, REACH & SvHC materials compliant

Applications

- Data centers, premise installations, telecommunication networks
- Ethernet, Fiber Channel, ATM, LAN, MAN and WAN
- Data communication and telecommunication networks
- Indoor/outdoor applications

Specifications

ELEMENT	CHARACTERISTIC
Height (mm)	235
Width (mm)	205
Depth (mm)	60
Net weight (kg)	0.9
Suitable for adapter type	SC Simplex
Number of ports	12
Cable entry	2
Material	ABS
Colour	Grey RAL 7035
Operating temperature (°C)	-40 to +60
Designed in accordance with	TIA/EIA 568.C, ISO/IEC 11801, EN50173, IEC60304, IEC61754,
Materials Compliant to	RoHS, Reach/SVHC

Ordering Information

Code	Fibre Type	Code	Fibre Count	Code	End A	Code
F	S SM Adaptors	WC	12 12F	DX	A LC	X-35AD
	M MM Adaptors		24 24F (LC Duplex)		B LCA	
	V MM EV adaptors				D SC	
					E SCA	
					L E2	
					M E2A	

PART NUMBER	DESCRIPTION	LEGACY PART NUMBER
FMWC12DXDX-35AD	IP Rated Wall Box Grey 7035 IP65 12 Port (SCS/LCD) 12F SC MM (Adaptors)	W35SCM12
FSWC12DXDX-35AD	IP Rated Wall Box Grey 7035 IP65 12 Port (SCS/LCD) 12F SC SM (Adaptors)	W35SCS12
FSWC12DXEX-35AD	IP Rated Wall Box Grey 7035 IP65 12 Port (SCS/LCD) 12F SCA SM (Adaptors)	W35SCA12
FMWC24DXAX-35AD	IP Rated Wall Box Grey 7035 IP65 12 Port (SCS/LCD) 24F LC MM (Adaptors)	W35LCM12
FVWC24DXAX-35AD	IP Rated Wall Box Grey 7035 IP65 12 Port (SCS/LCD) 24F LC MM EV (Adaptors)	W35LCV12
FSWC24DXAX-35AD	IP Rated Wall Box Grey 7035 IP65 12 Port (SCS/LCD) 24F LC SM (Adaptors)	W35LCS12
FSWC24DXBX-35AD	IP Rated Wall Box Grey 7035 IP65 12 Port (SCS/LCD) 24F LCA SM (Adaptors)	W35LCA12
FMWC12DXLX-35AD	IP Rated Wall Box Grey 7035 IP65 12 Port (SCS/LCD) 12F E2 MM (Adaptors)	W35E2M12
FSWC12DXLX-35AD	IP Rated Wall Box Grey 7035 IP65 12 Port (SCS/LCD) 12F E2 SM (Adaptors)	W35E2S12
FSWC12DXMX-35AD	IP Rated Wall Box Grey 7035 IP65 12 Port (SCS/LCD) 12F E2A SM (Adaptors)	W35E2A12